


## Metric Nylon Cable Glands

**Material:** PA6 Nylon for Gland  
 TPV for Seal  
 NBR for o-ring (on request) TPV for washer (on request)  
**Temperature Range:** -20° to +100 permanent  
 up to +150 intermittent  
**Ingress Protection Rating:** IP68 5 bar when it is used with o-ring or washer  
**Flame Retardancy:** V2 according to UL94 / V0 (on request)  
**Standards:** EN50262 Metric EN60423

- \* Standard Metric threaded nylon cable glands
- \* TPV sealing provide strong Cable Grip, Strain Relief and Superior Ingress Protection
- \* With its unique Anti-Click design, provides Anti-Vibration
- \* Easy Assembly
- \* Halogen Free
- \* Accessories such as locknut and o-ring must be ordered separately.




\* Long thread ones (15 mm.) is supplied on request. Please add 'Long' after Part Code!

\* Any other color can be supplied on request. Please add color name after Part Code!  
 For example: MCG01-Black



\* Some approvals do not cover all sizes!



Entry Thread Size	Light Grey RAL7035 Code	Cable Range		H mm	GL mm	Wrench mm
		Inch	mm.			
M 12 x 1,5	MCG01-L	.12-.26	3-6,5	24	8	15
M 16 x 1,5	MCG02-L	.15-.32	4-8	28	8	19
M 16 x 1,5	MCG03-L	.19-.39	5-10	29	10	22
M 20 x 1,5	MCG04-L	.15-.39	4-10	29	10	24
M 20 x 1,5	MCG05-L	.23-.47	6-12	29	10	24
M 20 x 1,5	MCG06-L	.39-.55	10-14	33	10	27
M 25 x 1,5	MCG07-L	.35-.67	9-17	38	10	33
M 25 x 1,5	MCG08-L	.51-.71	13-18	38	10	33
M 25 x 1,5	MCG09-L	.43-.67	11-17	35	10	29
M 25 x 1,5	MCG10-L	.35-.55	9-14	35	10	29
M 25 x 1,5	MCG11-L	.15-.39	4-10	32	10	29
M 25 x 1,5	MCG12-L	.23-.47	6-12	32	10	29
M 32 x 1,5	MCG13-L	.70-.98	18-25	41	10	42
M 40 x 1,5	MCG14-L	.87-1.26	22-32	51	10	53
M 50 x 1,5	MCG15-L	1.18-1.49	30-38	53	18	60
M 63 x 1,5	MCG16-L	1.33-1.73	34-44	55	18	70