

PG/Metric/DIN Type Cable Glands

Material: PA6 Nylon +30% GF)for Gland

TPV for Seal

NBR for o-ring (on request) Polystyrene for inner washer

Temperature Range: -20°to +100 permanent

Ingress Protection Rating: IP54


Flame Reterdancy: V2 according to UL94

Standards: DIN Type PG / Metric



* PG/Metric threaded DIN type nylon cable glands

* Accessories such as locknut and o-ring must be ordered separately.



*** Other colors can be supplied as per request. Please add color name after Part Code!!**

For example: PDCG01-Black

Entry Thread Size	Light Grey RAL7035 Code	Cable Range		H	GL	Wrench
		Inch	mm.	mm	mm	mm
PG7	PDCG01-L	.14-.24	3,5-6	21	8	15
PG9	PDCG02-L	.18-.28	4,5-7	22	8	19
PG11	PDCG03-L	.24-.35	6-9	22	8	22
PG13,5	PDCG04-L	.31-.51	8-13	26	9	24
PG16	PDCG05-L	.43-.55	11-14	28	10	27
PG21	PDCG06-L	.55-.71	14-18	32	11	33
PG29	PDCG07-L	.71-.98	18-25	35	11	42
PG36	PDCG08-L	.98-1.26	25-32	39	13	53
M12x1,5	MDCG01-L	.14-.24	3,5-6	21	8	15
M16x1,5	MDCG02-L	.18-.28	4,5-7	22	8	19
M16x1,5	MDCG03-L	.24-.35	6-9	22	8	22
M20x1,5	MDCG04-L	.31-.51	8-13	26	9	24
M20x1,5	MDCG05-L	.43-.55	11-14	28	10	27
M25x1,5	MDCG06-L	.55-.71	14-18	32	11	33

WE ALSO STOCK

NYLON ELBOW CABLE GLANDS
Pls ask our Sales Team

