

Metric Metallic Cable Glands

Material: Nickel Plated Brass / AISI303 or 316L SS for Gland
 TPV for Seal
 PA6 Nylon for Clamping Insert
 NBR for o-ring


Temperature Range: -20° to +100 permanent
 -40° to +150 intermittent

Ingress Protection Rating: IP68 5 bar

Flame Retardancy: V2 according to UL94

Standards: DIN EN 62444/50262 Metric EN 60423

- * Metric threaded metallic cable glands
- * TPV sealing provide strong Cable Grip, Strain Relief and Superior Ingress Protection
- * For standard industrial applications in harsh environments.
- * Easy Assembly
- * Accessories such as locknut must be ordered separately.



* For AISI 316L Stainless Steel ones
 Please add '316' after Part Code!

* For 25mm thread length please add
 '25' after Part Code!

* All other size and cable dia. options
 available upon request...



* Some approvals do not cover all sizes!

* NPT Thread available on request!

Entry Thread Size	Code Brass	Code Stainless Steel	Cable Range		H mm	GL mm	Wrench Size	
			Inch	mm.			B mm.	C mm.
M12x1,5	MBCG01	MSSCG01	.12-.26	3-6,5	22	6	14	14
M16x1,5	MBCG02	MSSCG02	.15-.32	4-8	23	7	18	17
M20x1,5	MBCG03	MSSCG03	.15-.39	4-10	26,5	8	22	22
M20x1,5	MBCG04	MSSCG04	.23-.47	6-12	26,5	8	22	22
M25x1,5	MBCG05	MSSCG05	.39-.55	10-14	28	8	27	24
M32x1,5	MBCG06	MSSCG06	.51-.71	13-18	31,5	9	34	30
M40x1,5	MBCG07	MSSCG07	.70-.98	18-25	38	9	43	40
M50x1,5	MBCG08	MSSCG08	.87-1.26	22-32	43	9	55	50
M63x1,5	MBCG09	MSSCG09	1.30-1.73	33-44	48	14	68	64
M12x1,5	MBCG10	MSSCG10	.12-.26	3,5-6	22	12	14	14
M16x1,5	MBCG11	MSSCG11	.15-.32	4-8	23	12	18	17
M20x1,5	MBCG12	MSSCG12	.15-.39	4-10	26,5	12	22	22
M20x1,5	MBCG13	MSSCG13	.23-.47	6-12	26,5	12	22	22
M25x1,5	MBCG14	MSSCG14	.39-.55	10-14	28	12	27	24
M32x1,5	MBCG15	MSSCG15	.51-.71	13-18	31,5	14	34	30
M40x1,5	MBCG16	MSSCG16	.70-.98	18-25	38	14	43	40
M50x1,5	MBCG17	MSSCG17	.87-1.26	22-32	43	14	55	50
M63x1,5	MBCG18	MSSCG18	1.30-1.73	33-44	48	18	70	64