

NPT Nylon Cable Glands


Material: PA6 Nylon for Gland
 CR for Seal
 NBR for o-ring (on request) TPV for washer (on request))
Temperature Range: -20° to +100 permanent
 up to +150 intermittent
Ingress Protection Rating: IP68 5 bar when it is used with o-ring or washer
Flame Retardancy: V2 according to UL94 / V0 (on request)
Standards: NPT ANSI B1.20.1



- * Standard NPT threaded nylon cable glands
- * CR sealing provide strong Cable Grip, Strain Relief and Superior Ingress Protection
- * With its unique provides Anti-Vibration
- * Easy Assembly
- * Halogen Free
- * Accessories such as locknut and o-ring must be ordered separately.



* Some approvals do not cover all sizes!



* Any other colors can be supplied as per request. Please add color name after Part Code!
 For example: NCG01-Black



Entry Thread Size	Light Grey RAL7035 Code	Cable Range		H	GL	Wrench
		Inch	mm.	mm	mm	mm
NPT 3/8"	NCG01-L	.12-.28	3-7	32.2	15	22
NPT 3/8"	NCG02-L	.19-.39	5-10	32.2	15	22
NPT 1/2"	NCG03-L	.20-.35	5-9	32.4	15	24
NPT 1/2"	NCG04-L	.23-.47	6-12	32.4	15	24
NPT 1/2"	NCG05-L	.28-.47	7-12	31.9	15	27
NPT 1/2"	NCG06-L	.39-.55	10-14	31.9	15	27
NPT 3/4"	NCG07-L	.35-.63	9-16	38.4	15	33
NPT 3/4"	NCG08-L	.51-.71	13-18	38.4	15	33
NPT 1"	NCG09-L	.47-.79	12-20	43.3	18	42
NPT 1"	NCG010-L	.70-.98	18-25	43.3	18	42