

PG Metallic Cable Glands

Material: Nickel Plated Brass / AISI303 or 316L SS for Gland
 TPV for Seal
 PA6 Nylon for Clamping Insert
 NBR for o-ring


Temperature Range: -20° to +100 permanent
 -40° to +150 intermittent

Ingress Protection Rating: IP68 5 bar

Flame Retardancy: V2 according to UL94

Standards: DIN EN 62444/50262 PG DIN 40430

- * PG threaded metallic cable glands
- * TPV sealing provide strong Cable Grip, Strain Relief and Superior Ingress Protection
- * For standard industrial applications in harsh environments.
- * Easy Assembly
- * Accessories such as locknut must be ordered separately.



* For AISI 316L Stainless Steel ones Please add '316' after Part Code! For example: PSSCG01-316

* For 25mm thread length please add '25' after Part Code! For example: PBCG01-25



* Some approvals do not cover all sizes!

* All other size and cable dia. options available upon request...

Entry Thread Size	Code Brass	Code Stainless Steel	Cable Range		H mm	GL mm	Wrench mm.
			Inch	mm.			
PG7	PBCG01	PSSCG01	.12-.26	3-6,5	22	6	14
PG9	PBCG02	PSSCG02	.15-.32	4-8	23	6	17
PG11	PBCG03	PSSCG03	.19-.39	5-10	24,5	6	20
PG13.5	PBCG04	PSSCG04	.15-.39	4-10	26,5	6,5	22
PG13.5	PBCG05	PSSCG05	.23-.47	6-12	26,5	6,5	22
PG16	PBCG06	PSSCG06	.39-.55	10-14	28	6,5	24
PG21	PBCG07	PSSCG07	.51-.71	13-18	31,5	7	30
PG29	PBCG08	PSSCG08	.70-.98	18-25	38	8	40
PG36	PBCG09	PSSCG09	.87-1.26	22-32	43	10	50
PG42	PBCG10	PSSCG10	1.18-1.49	30-38	47	12	57
PG48	PBCG11	PSSCG11	1.30-1.73	33-44	48	14	64
PG7	PBCG12	PSSCG12	.12-.26	3,5-6	22	10	14
PG9	PBCG13	PSSCG13	.15-.32	4-8	23	10	17
PG11	PBCG14	PSSCG14	.19-.39	5-10	24,5	10	20
PG13.5	PBCG15	PSSCG15	.15-.39	4-10	26,5	10	22
PG13.5	PBCG16	PSSCG16	.23-.47	6-12	26,5	10	22
PG16	PBCG17	PSSCG17	.39-.55	10-14	28	10	24
PG21	PBCG18	PSSCG18	.51-.71	13-18	31,5	12	30
PG29	PBCG19	PSSCG19	.70-.98	18-25	38	12	40
PG36	PBCG20	PSSCG20	.87-1.26	22-32	43	14	50
PG42	PBCG21	PSSCG21	1.18-1.49	30-38	47	18	60
PG48	PBCG22	PSSCG22	1.30-1.73	33-44	48	18	65