

## PG Nylon Cable Glands

**Material:** PA6 Nylon for Gland  
 TPV for Seal  
 NBR for o-ring (on request) TPV for washer (on request)


**Temperature Range:** -20° to +100 permanent  
 up to +150 intermittent

**Ingress Protection Rating:** IP68 5 bar when it is used with o-ring or washer

**Flame Retardancy:** V2 according to UL94 / V0 (on request)

**Standards:** EEN50262 PG DIN40430

- \* Standard PG threaded nylon cable glands
- \* TPV sealing provide strong Cable Grip, Strain Relief and Superior Ingress Protection
- \* With its unique Anti-Click design, provides Anti-Vibration
- \* Easy Assembly
- \* Halogen Free
- \* Accessories such as locknut and o-ring must be ordered separately.




\* Long thread ones (15 mm.) is supplied on request. Please add 'Long' after Part Code!

\* Any other colors can be supplied as per request. Please add color name after Part Code! For example: PCG01-Black



\* Some approvals do not cover all sizes!



Entry Thread Size	Light Grey RAL7035 Code	Cable Range		H mm	GL mm	Wrench mm
		Inch	mm.			
PG7	PCG01-L	.12-.26	3-6,5	24	8	15
PG9	PCG02-L	.15-.32	4-8	28	8	19
PG11	PCG03-L	.19-.39	5-10	29	8	22
PG13,5	PCG04-L	.15-.39	4-10	29	9	24
PG13,5	PCG05-L	.23-.47	6-12	29	9	24
PG16	PCG06-L	.39-.55	10-14	33	9	27
PG21	PCG07-L	.35-.67	9-17	38	11	33
PG21	PCG08-L	.51-.71	13-18	38	11	33
PG29	PCG09-L	.70-.98	18-25	41	11	42
PG36	PCG10-L	.87-1.26	22-32	51	13	53
PG42	PCG11-L	1.18-1.49	30-38	55	13	60
PG48	PCG12-L	1.33-1.73	34-44	55	14	65