


PVC Coated Steel Conduits

LSF Cover (on request)

Technical Details:

- Material: PVC, self extinguishing / **LSF (on request)**
- Main usage: Applications in machine tool and connections for general wiring where light mechanical stress can be obtained.
- Temp range: -20°C till +80°C
- Protection: IP40
- Standards: BS EN 61386 High Impact Resistance
- Colour: Black (Grey or other color on request)
- Full-Shrink packing



Code	Code		Inner & Outer Dia. (mm.)	Coil Size (mt.)
	Metric	NPT		
OPGSC7	12		7,5-11,5	50
OPGSC9	16	1/4'	9-13	50
OPGSC11	16	3/8'	11-15	50
OPGSC16	20	1/2'	16-20	50
OPGSC21	25	3/4'	21-25	50
OPGSC26	32	1'	26-31	25
OPGSC35		1 1/4'	35-40	25
OPGSC37	40		37-42	25
OPGSC40	50	1 1/2'	40-45	25
OPGSC51	63	2'	51-56	25
OPGSC63		2 1/2'	63-68	25
OPGSC75		3'	75-83	25

* Dimensions may undergo changes and deviations.



* This product can also be supplied with a draw wire. Please add "dw" after part code

* Other coil sizes available upon request. Please add requested coil size after part code. For example: OPGSC7-10

WE ALSO STOCK

FULL RANGE OF CONTRACTOR PACKS SEE PAGES 42-43

