


Technical Details:

- Main usage: Applications indoor & outdoor where mechanical strength is needed
- Material: Thermoplastic base with PVC plastic coating and reinforced PVC spiral core, smooth bore
- Temp range: +5°C till +65 °C
- Color: Black / Grey (on request)
- Standards: BS EN 61386 Crush resistance to 320 N



Code	Inner Dia. (mm.)	Outer Dia. (mm.)	Coil Size (mt.)
OPVCS08	8	12	30
OPVCS10	10	14,5	30
OPVCS12	12	16,3	30
OPVCS16	16	20,5	30
OPVCS20	20	24,7	30
OPVCS25	25	30,3	30
OPVCS32	32	37,5	30
OPVCS40	40	46,2	30
OPVCS50	50	57	30



* For Grey color please add "G" after part code.

Spiral Glands



Code		Size		Conduit Size
Metric	PG	Metric	PG	
OMSCG12	OPSCG12	M12x1,5	PG7	8
OMSCG16	OPSCG16	M16x1,5	PG9	10
OMSCG116	OPSCG116	M16x1,5	PG11	12
OMSCG20	OPSCG20	M20x1,5	PG13,5	16
OMSCG120	OPSCG120	M20x1,5	PG16	20
OMSCG25	OPSCG25	M25x1,5	PG21	25
OMSCG32	OPSCG32	M32X1,5	PG29	32
OMSCG40	OPSCG40	M40x1,5	PG29	40
OMSCG50	OPSCG50	M50x1,5	PG36	50
OMSCG63	OPSCG63	M63x1,5	PG48	50