

PG/Metric/NPT Strain Relief Cable Glands

Material: PA6 Nylon for Gland

TPV for Seal

NBR for o-ring (on request) TPV for washer (on request))


Temperature Range: -20° to +100 permanent
up to +150 intermittent

Ingress Protection Rating: IP68 5 bar when it is used with o-ring or washer

Flame Retardancy: V2 according to UL94 / V0 (on request)

Standards: EN50262 PG DIN40430

- * Standard PG/Metric/NPT threaded nylon cable glands
- * TPV sealing provide strong Cable Grip, Strain Relief and Superior Ingress Protection
- * With its unique design, provides excellent cable bending protection
- * Easy Assembly
- * Halogen Free
- * Accessories such as locknut and o-ring must be ordered separately.



* Long thread ones (15 mm.) is supplied on request. Please add 'Long' after Part Code!

* Any other colors can be supplied as per request. Please add color name after Part Code! For example: PSCG01-Black



* NPT Thread available on request!

Entry Thread Size	Light Grey RAL7035 Code	Cable Range		H mm	GL mm	Wrench mm
		Inch	mm.			
PG7	PSCG01-L	.12-.26	3-6,5	57	8	15
PG9	PSCG02-L	.15-.32	4-8	70	8	19
PG11	PSCG03-L	.19-.39	5-10	81	8	22
PG13,5	PSCG04-L	.15-.39	4-10	89	9	24
PG13,5	PSCG05-L	.23-.47	6-12	89	9	24
PG16	PSCG06-L	.39-.55	10-14	107	9	27
PG21	PSCG07-L	.35-.67	9-17	124	11	33
PG21	PSCG08-L	.51-.71	13-18	124	11	33
M12x1,5	MSCG01-L	.12-.26	3-6,5	57	8	15
M16x1,5	MSCG02-L	.15-.32	4-8	70	8	19
M16x1,5	MSCG03-L	.19-.39	5-10	81	10	22
M20x1,5	MSCG04-L	.15-.39	4-10	89	10	24
M20x1,5	MSCG05-L	.23-.47	6-12	89	10	24
M20x1,5	MSCG06-L	.39-.55	10-14	107	10	27
M25x1,5	MSCG07-L	.35-.67	9-17	124	10	33
M25x1,5	MSCG08-L	.51-.71	13-18	124	10	33