

PP – Polypropylene Conduit Contractor Pack

- Main usage: General use, industrial where limited mechanical protection is required
- Material: Polypropylene PP, self extinguishing
- Temp range: -20°C till +90°C
- Color: Black / Grey
- BS EN 61386 Crush resistance to 320 N

Pack contents:

- 10 meter conduit
- 10 locknut's
- 10 straight fitting
- 10 conduit clips can be added on request



Code	Conduit & Gland Size	Coil Length (mt.)
OPPCP16	16	10
OPPCP20	20	10
OPPCP25	25	10
OPPCP32	32	10

* All other size & color options available upon request..

PA6 Nylon Conduit Contractor Pack

- Main usage: Machine tool, public buildings, industrial where limited mechanical protection is required
- Material: Polyamide PA6 nylon conduit, halogen free, low toxicity & smoke density
- Self extinguishing
- Temp range: -40°C till +120°C
- Standards: EN 61386
- Crush resistance to 320 N



Pack contents:

- 10 meter conduit
- 10 straight fittings
- 10 locknut's
- 10 conduit clips can be added on request



Code	Conduit & Gland Size	Coil Length (mt.)
OPACP16	16	10
OPACP20	20	10
OPACP25	25	10
OPACP32	32	10

* All other size options available upon request..

Flexible Spiral – PVC Conduit Contractor Pack

- Main usage: Applications indoor & outdoor where mechanical strength is needed
- Material: Thermoplastic base with PVC plastic coating and reinforced PVC spiral core, smooth bore
- Temp range: +5°C till +65 °C
- Color: Black / Grey
- BS EN 61386 Crush resistance to 320 N



Pack contents:

- 10 meter conduit
- 10 spiral glands
- 10 locknut's

Code	Conduit & Gland Size	Coil Length (mt.)
OPVCCP16	16	10
OPVCCP20	20	10
OPVCCP25	25	10
OPVCCP32	32	10