

# PE Coil Pipe Halogen Free

## PE Coil Pipe Light Gauge

**Application Fields:** Used in buildings and prefabs, flush mounted and surface mounted applications, concrete and screed, walls and suspended ceilings, tunnel formwork applications, under plaster and electrical installations where low mechanical stress is expected.

<b>Technical Properties</b>	Material	: PE based Thermoplastic	
	Compression Resistance	: 320 Newton/ 60 sec / 23±2°C	Class 2
	Impact Resistance	: 2 kg/100 mm/ - 25°C	Class 3
	Minimum Ambient Temperature	: - 25°C	Class 4
	Maximum Ambient Temperature	: + 60°C	Class 1

Nominal Diameter	Ø 14	Ø 16	Ø 18	Ø 20	Ø 25	Ø 32	Ø 40	Ø 50	Ø 63	Ø 75	Ø 90
Outside Diameter (mm)	14 <sub>-0.3</sub>	16 <sub>-0.3</sub>	18 <sub>-0.3</sub>	20 <sub>-0.3</sub>	25 <sub>-0.4</sub>	32 <sub>-0.4</sub>	40 <sub>-0.4</sub>	50 <sub>-0.4</sub>	63 <sub>-0.6</sub>	75 <sub>-0.6</sub>	90 <sub>-0.8</sub>
Inside Diameter (mm)	11,5	13,2	15,0	17,1	21,4	27,8	35,0	44,4	57,0	68,2	82,4
Roll Length (m)	200	200	200	200	100	100	100	100	100	100	50
Item Code	OP1 014	OP1 016	OP1 018	OP1 020	OP1 025	OP1 032	OP1 040	OP1 050	OP1 063	OP1 075	OP1 090
Item Code (With Wire Puller)	OP1 114	OP1 116	OP1 118	OP1 120	OP1 125	OP1 132	OP1 140	OP1 150	OP1 163	OP1 175	OP1 190

### COLOUR



## PE Coil Pipe Heavy Gauge

**Application Fields:** Used in buildings and prefabs, flush mounted and surface mounted applications, concrete and screed, walls and suspended ceilings, tunnel formwork applications, under plaster and electrical installations where high mechanical stress is expected.

<b>Technical Properties</b>	Material	: PE based Thermoplastic	
	Compression Resistance	: 750 Newton/ 60 sec / 23±2°C	Class 3
	Impact Resistance	: 2 kg/100 mm/ - 25°C	Class 3
	Minimum Ambient Temperature	: - 25°C	Class 4
	Maximum Ambient Temperature	: + 60°C	Class 1

Nominal Diameter	Ø 14	Ø 16	Ø 18	Ø 20	Ø 25	Ø 32	Ø 40	Ø 50	Ø 63	Ø 75	Ø 90
Outside Diameter (mm)	14 <sub>-0.3</sub>	16 <sub>-0.3</sub>	18 <sub>-0.3</sub>	20 <sub>-0.3</sub>	25 <sub>-0.4</sub>	32 <sub>-0.4</sub>	40 <sub>-0.4</sub>	50 <sub>-0.4</sub>	63 <sub>-0.6</sub>	75 <sub>-0.6</sub>	90 <sub>-0.8</sub>
Inside Diameter (mm)	11,0	12,4	14,0	16,0	20,1	25,4	32,6	42,0	54,4	65,6	79,6
Roll Length (m)	200	200	200	200	100	100	100	100	100	100	50
Item Code	OP3 014	OP3 016	OP3 018	OP3 020	OP3 025	OP3 032	OP3 040	OP3 050	OP3 063	OP3 075	OP3 090
Item Code (With Wire Puller)	OP3 114	OP3 116	OP3 118	OP3 120	OP3 125	OP3 132	OP3 140	OP3 150	OP3 163	OP3 175	OP3 190

### COLOUR

