

**PE V0
Coil Pipe**
Halogen Free
Self-extinguishing

PE V0 Coil Pipe Light Gauge

Application Fields: Used in buildings and prefabs, flush mounted and surface mounted applications, concrete and screed, walls and suspended ceilings, tunnel formwork applications, under plaster and electrical installations where low mechanical stress is expected.

Technical Properties	Material	: PE based Thermoplastic	
	Compression Resistance	: 320 Newton/ 60 sec / 23±2°C	Class 2
	Impact Resistance	: 2 kg/100 mm/ - 25°C	Class 3
	Minimum Ambient Temperature	: - 25°C	Class 4
	Maximum Ambient Temperature	: + 60°C	Class 1

Nominal Diameter	Ø 14	Ø 16	Ø 18	Ø 20	Ø 25	Ø 32	Ø 40	Ø 50	Ø 63	Ø 75	Ø 90
Outside Diameter (mm)	14 _{-0,3}	16 _{-0,3}	18 _{-0,3}	20 _{-0,3}	25 _{-0,4}	32 _{-0,4}	40 _{-0,4}	50 _{-0,4}	63 _{-0,6}	75 _{-0,6}	90 _{-0,8}
Inside Diameter (mm)	11,5	13,2	15,0	17,1	21,4	27,8	35,0	44,4	57,0	68,2	82,4
Roll Length (m)	200	200	200	200	100	100	100	100	100	100	50
Item Code	OH1 014	OH1 016	OH1 018	OH1 020	OH1 025	OH1 032	OH1 040	OH1 050	OH1 063	OH1 075	OH1 090
Item Code (With Wire Puller)	OH1 114	OH1 116	OH1 118	OH1 120	OH1 125	OH1 132	OH1 140	OH1 150	OH1 163	OH1 175	OH1 190

COLOUR



PE V0 Coil Pipe Heavy Gauge

Application Fields: Used in buildings and prefabs, flush mounted and surface mounted applications, concrete and screed, walls and suspended ceilings, tunnel formwork applications, under plaster and electrical installations where high mechanical stress is expected.

Technical Properties	Material	: PE based Thermoplastic	
	Compression Resistance	: 750 Newton/ 60 sec / 23±2°C	Class 3
	Impact Resistance	: 2 kg/100 mm/ - 25°C	Class 3
	Minimum Ambient Temperature	: - 25°C	Class 4
	Maximum Ambient Temperature	: + 60°C	Class 1

Nominal Diameter	Ø 14	Ø 16	Ø 18	Ø 20	Ø 25	Ø 32	Ø 40	Ø 50	Ø 63	Ø 75	Ø 90
Outside Diameter (mm)	14 _{-0,3}	16 _{-0,3}	18 _{-0,3}	20 _{-0,3}	25 _{-0,4}	32 _{-0,4}	40 _{-0,4}	50 _{-0,4}	63 _{-0,6}	75 _{-0,6}	90 _{-0,8}
Inside Diameter (mm)	11,0	12,4	14,0	16,0	20,1	25,4	32,6	42,0	54,4	65,6	79,6
Roll Length (m)	200	200	200	200	100	100	100	100	100	100	50
Item Code	OH3 014	OH3 016	OH3 018	OH3 020	OH3 025	OH3 032	OH3 040	OH3 050	OH3 063	OH3 075	OH3 090
Item Code (With Wire Puller)	OH3 114	OH3 116	OH3 118	OH3 120	OH3 125	OH3 132	OH3 140	OH3 150	OH3 163	OH3 175	OH3 190

COLOUR

